

*** **SP-710V-FD**TRAILER-MOUNTED SPEED SIGN

Ver-Mac's SP-710V-FD is a battery/solar-powered fold down style trailer-mounted speed sign, with 2-digit display. It features our Stealth Technology, V-Touch SP controller, JamLogic® Fleet Management Software and state-of-the-art doppler radar. Our speed sign is designed to display real-time speed information to the motoring public, reducing speeds and providing a safer environment. The SP-710V-FD is perfect to provide speed awareness to highway construction projects, school zones and urban areas.



MUTCD COMPLIANT



V-TOUCH SP CONTROLLER

EASY-TO-READ

3.75 in (95 mm) pressure-sensitive black and white display screen with intuitive interface

INTUITIVE ICONS

Quickly select speed parameters and blink option

BACKLIT SCREEN

Perfect for nighttime use

REAL-TIME DISPLAY

View speed display, battery voltage level and other key elements

STEALTH MODE

No speed is displayed, but data is collected*

OPTIONAL WARNING DEVICES

Easy to integrate flashing beacons, strobe lights, red and blue flashing bar and audible alarm

*Requires data logger option

STEALTH TECHNOLOGY

CLEVERLY HIDDEN BATTERY COMPARTMENT

Deter thieves from stealing batteries

LONG-LASTING SEALED BATTERIES

No maintenance required

DOPPLER RADAR

- Picks up average speed and vehicle count at up to 2000 ft
- Up to 2 lanes / directional
- · No calibration necessary
- Integrated into the sign

JAMLOGIC® FLEET MANAGEMENT SOFTWARE (OPTIONAL)

Equip the SP-710V-FD with a high speed modem with GPS to monitor and collect data with JamLogic automation. All the data is stored in the JamLogic software. Run your own reports monthly, weekly, daily or custom plus export them to excel. JamLogic allows you to have all the traffic data at your fingertips.

STATISTICS (OPTIONAL)

This option allows you to collect average speed and number of vehicles approaching (directional). The data can be downloaded via a USB key at the trailer or remotely through JamLogic (modem option required).

APPLICATIONS

- Law enforcement
- Speed awareness
- Smart work zones
- Traffic studies

DISPLAY

- Speed display sign: 25 x 42 in (662 mm x 1073 mm)
- Display: 2 digits (mph)
- 18 in characters—visible up to 305 m (1000 ft)
- 4 LEDs per pixel
- Can accomodate 24 x 36 in. (610 x 914 mm) work zone static sign and 36 x 48 in. (914 x 1219 mm) or 48 x 60 in. (1219 x 1524 mm) or up to 48 x 72 in. (1219 x 1829 mm) speed static signs not included
- Plug & play display modules for simplified maintenance

DIMENSIONS AND WEIGHTS

- Operating height: 164 in. (4158 mm)
- Operating length: 142 in. (3617 mm)
- Overall width: 70 in. (1790 mm)
- Traveling height: 87 in. (2210 mm)
- Traveling length: 167 in. (4241 mm)
- Weight (approx.): 1145 lb (519 kg)

OPTIONS

- Battery charger
- Modem with GPS
- Data automation (statistics)
- Tongue wheel jack

Other options are available to meet your needs.

POWER SUPPLY CONFIGURATION

OPTI POWER LENS

Designed to maximize each LED output and utilize less energy.

SOLAR PANEL

Provides maximum solar recharging during all four seasons.

 The standard battery/solar configuration is designed to run 12 months in most regions without manual charging

HIGH-OUALITY CONSTRUCTION

POWDER COATING SUPERIOR FINISH

Impact, humidity, salt spray and rust resistant

4 ADJUSTABLE STABILIZER LEGS

For stabilization and easy deployment and transportation

REMOVABLE TONGUE

Saves space for storage

MANUAL LIFT MECHANISM

For quick deployment

HEAVY-DUTY PLASTIC FENDERS

For durability and easy replacement

2-IN. (51 MM) COUPLER OR 3-IN. (76 MM) PINTLE EYE

For easy towing



WARRANTY

- 1 year on complete trailer
- 2 years on electronic components manufactured by Ver-Mac





