

PORTABLE TRAFFIC SIGNALS

Ver-Mac's TLG-1408 and TLG-1412 are battery powered portable traffic signal trolley sets with a traffic signal head on both trolleys. They come respectively with 8 in. (203 mm) and 12 in. (305 mm) LED lamps. Both systems are timed and use GPS for synchronization. The TLG models feature the V-Touch TLG controller and V-SWAP system. They are perfect for simple short term applications.



TLG-1412

V-TOUCH TLG CONTROLLER

Ver-Mac's V-Touch TLG is the industry's most easy-to-use controller.

- Compact 3.75 in. (95 mm) black and white graphic touch screen
- Intuitive point-and-go icons
- Real-time signal display and battery voltage level

The V-Touch TLG features four easy programming options:

BY DISTANCE

The operator determines the distance between signals and the controller calculates duration automatically

The operator can manually enter green and clearance times

PREPROGRAMMED

Select among 18 preprogrammed codes

ADVANCED

The operator determines the distance between signals and the approximate vehicles' speed in the work zone. The controller automatically calculates duration with more accuracy.





Solar panel option



Travel position

TLG-1408/TLG-1412 FEATURES

V-TOUCH TLG CONTROLLER

Intuitive icons for quick and easy programming—no training required

V-SWAP SYSTEM

Allows to remove and charge batteries without having to stop the signal on an active job

GPS TIME SYNCHRONIZATION

Ensures that the time on the two signals operate in unison

TELESCOPIC MAST

For quick, easy and effortless deployment

V-SWAP SYSTEM

Our TLG-1408 and TLG-1412 traffic signals can be equipped with two 12-volt batteries. The signal operates on one battery with an auxiliary battery back-up. The V-SWAP system recognizes low voltages and automatically switches to the auxiliary battery. It allows users to remove and charge batteries without having to stop the signal on an active job.

SOLAR PANEL (OPTIONAL)

Add a solar panel kit to your traffic signals and get more autonomy from them!

APPLICATIONS

- Urban zones
- Advertising / Special Events
- Bridge construction/repair
- Secondary roads
- Mountainous Work zone construction

DIMENSIONS AND WEIGHT

- Overall length: 32 in. (824 mm)
- Overall width: 23 in. (587 mm)
- Traveling height: 81 in. (2054 mm)
- Operating height: 137 in. (3480 mm)
- Weight (approx.)*: TLG-1408: 140 kg (309 lb.) TLG-1412: 145 kg (320 lb.)

OPTIONS

- 12-volt batteries
- · Battery charger
- Countdown display
- Solar panel

Other options are available to meet your needs.

WARRANTY

- 1-year warranty on complete trolleys
- 2-year warranty on electronic components manufactured by Ver-Mac





^{*}Weight including batteries